



KOKYBĖS SERTIFIKATAS
CERTIFICATE OF QUALITY · ПАСПОРТ КАЧЕСТВА

Fanfaro TSE 5W-30			
PRODUCT DESIGNATION	SAE 5W-30 API SL/CF, ACEA A3/B3 MB 229.1 VW 500.00/505.00		
Control Item	Standard	Results	Test Method
Viscosity at 100 °C, cSt	11.0-12.0	11.18	ASTM D-445
Viscosity at 40 °C, cSt	-	66.37	ASTM D-445
Dynamic viscosity [mPa.s], at -30 °C, max.	6600	5240	ASTM D 5293
Viscosity Index, min.	140	161	ASTM D-2270
Flash point, open cup, °C min	220	224	ASTM D-92
Pour point, °C, max.	-35	-42	ASTM D-97
Total base no. mgKOH/g, min	8,0	8,60	ASTM D-2896
Density at 15 °C, kg/l, max.	0,9	0.852	ASTM D-1298

Responsible analyst: Daiva Burbaite

UAB "SCT LUBRICANTS"

ŠILUTĖS PL. 119, LT 95112 KLAIPĖDA, LIETUVA
TEL.: (8 46) 34 03 45, FAX. (8 46) 34 18 91
E-MAIL: KLAIPEDA@SCT.LT