



**KOKYBĖS SERTIFIKATAS**  
CERTIFICATE OF QUALITY · ПАСПОРТ КАЧЕСТВА

***FANFARO Compressor Oil ISO 46***

|                              |                 |   |                    |
|------------------------------|-----------------|---|--------------------|
| <b>PRODUCT DESIGNATION</b>   |                 |   |                    |
|                              |                 | ISO 46, ISO-L DAA/DAB/DAG/DAH<br>DIN 51506<br>VBL/VCL/VDL |                    |
| <b>Control Item</b>          | <b>Standard</b> | <b>Results</b>  | <b>Test Method</b> |
| Viscosity at 100 °C, cSt     | -               | 6.58  | ASTM D-445         |
| Viscosity at 40 °C, cSt      | 41.4-50.6       | 45.08   | ASTM D-445         |
| Viscosity Index, min.        | 90              | 96  | ASTM D-2270        |
| Flash point, open cup, °C    | 200             | 216   | ASTM D-92          |
| Pour point, °C, max.         | -30             | -30   | ASTM D-97          |
| Density at 15 °C, kg/l, max. | 0.9             | 0.883   | ASTM D-1298        |

Responsible analyst: Daiva Burbaite

**UAB "SCT LUBRICANTS"**

ŠILUTĖS PL. 119, LT 95112 KLAIPĖDA, LIETUVA  
TEL.: (8 46) 34 03 45, FAX. (8 46) 34 18 91  
E-MAIL: KLAIPEDA@SCT.LT