



**KOKYBĖS SERTIFIKATAS**  
CERTIFICATE OF QUALITY · ПАСПОРТ КАЧЕСТВА

<b>FANFARO GAZOLIN Formula GTL</b>			
<b>PRODUCT DESIGNATION</b>	<b>SAE 15W-40 API SG/CD</b>		
<b>Control Item</b>	<b>Standard</b>	<b>Results</b>	<b>Test Method</b>
Viscosity at 100 °C, cSt	13.5-14.5	14,10	ASTM D-445
Viscosity at 40 °C, cSt	-	105,40	ASTM D-445
Dynamic viscosity [ mPa.s ], at -20 °C, max.	7000	6820	ASTM D 5293
Viscosity Index, min.	130	135	ASTM D-2270
Flash point, open cup, °C	210	228	ASTM D-92
Pour point, °C, max.	-30	-35	ASTM D-97
Total base no. mgKOH/g, min	4,8	5,03	ASTM D-2896
Density at 15 °C, kg/l, max.	0,9	0.876	ASTM D-1298

Responsible analyst : Daiva Burbaite

**UAB "SCT LUBRICANTS"**

ŠILUTĖS PL. 119, LT 95112 KLAIPĖDA, LIETUVA  
TEL.: (8 46) 34 03 45, FAX. (8 46) 34 18 91  
E-MAIL: KLAIPEDA@SCT.LT