



KOKYBĖS SERTIFIKATAS
CERTIFICATE OF QUALITY · ПАСПОРТ КАЧЕСТВА

FANFARO Multifarm STOU 10W-40			
PRODUCT DESIGNATION	SAE10W-40 API CG-4,CF-4,CF,CE,CD,SE MB 227.1/228.1 ACEA E3 MAN 271 STOU:Massey Ferguson M1139,M1144,M1145 John Deere J27, Ford M2C159B/C, FNH 82009201/2/3, New Holland NH 030C and NH 024C UTTO: Massey Ferguson M1135,M1145, John Deere J20C, Ford M2C134D, New Holland NH410B and NH420A, Case New Holland(CNH)MAT 3525, MAT 3526 Gear and Transmission: ZF TEML 03A,05K,06A,B(includes 06R)&C, 07B&D, Allison C4, API GL-4 Hydraulic: Sperry Vickers/Eaton I-280-S&M2950S, Sauser Sunstrand/Danfoss-Hydro Tatic Trans Fluid, Afnor NFE68603E		
Control Item	Standard	Results	Test Method
Viscosity at 100 °C, cSt	12.5-14.5	13.99	ASTM D-445
Viscosity at 40 °C, cSt	-	96.17	ASTM D-445
Dynamic viscosity [mPa.s], at -25 °C, max.	7000	6820	ASTM D 5293
Viscosity Index, min.	140	148	ASTM D-2270
Flash point, open cup, °C min.	210	226	ASTM D-92
Pour point, °C, max.	-30	-35	ASTM D-97
Total base no. mgKOH/g, min	10.2	10.86	ASTM D-2896
Density at 15 °C, kg/l, max.	0.9	0.870	ASTM D-1298

Responsible analyst : Daiva Burbaite

UAB "SCT LUBRICANTS"

ŠILUTĖS PL. 119, LT 95112 KLAIPĖDA, LIETUVA
TEL.: (8 46) 34 03 45, FAX. (8 46) 34 18 91
E-MAIL: KLAIPEDA@SCT.LT