



KOKYBĖS SERTIFIKATAS
CERTIFICATE OF QUALITY · ПАСПОРТ КАЧЕСТВА

FANFARO TO-4 Powertrain Oil SAE 10W			
PRODUCT DESIGNATION	SAE 10W; Caterpillar TO-4; Komatsu KES 07.868.1; Allison C4(off-road)		
Control Item	Standard	Results	Test Method
Viscosity at 100 °C, cSt	4.5-7,5	5,83	ASTM D-445
Viscosity at 40 °C, cSt	-	35,62	ASTM D-445
Viscosity Index, min.	100	105	ASTM D-2270
Dinamic Viscosity by Brookfield, cP(mPa s), max , cP(mPa s(-35) °C)		84582	ASTM D2983
Flash point, open cup, °C	200	216	ASTM D-92
Pour point, °C, max.	-30	-34	ASTM D-97
Total base no. mgKOH/g, min	7,5	7,66	ASTM D-2896
Density at 15 °C, kg/l, max.	0.9	0.879	ASTM D-1298

Responsible analyst : Daiva Burbaite

UAB "SCT LUBRICANTS"

ŠILUTĖS PL. 119, LT 95112 KLAIPĖDA, LIETUVA
TEL.: (8 46) 34 03 45, FAX. (8 46) 34 18 91
E-MAIL: KLAIPEDA@SCT.LT