



**KOKYBĖS SERTIFIKATAS**  
CERTIFICATE OF QUALITY · ПАСПОРТ КАЧЕСТВА

<b>FANFARO TO-4 Powertrain Oil SAE 50</b>			
PRODUCT DESIGNATION	SAE 50; Caterpillar TO-4; Komatsu KES 07.868.1; Allison C4(off-road)		
Control Item	Standard	Results	Test Method
Viscosity at 100 °C, cSt	>16,3	18,45	ASTM D-445
Viscosity at 40 °C, cSt	-	212,0	ASTM D-445
Viscosity Index, min.	90	96	ASTM D-2270
Dinamic Viscosity by Brookfield, cP(mPa s), max		58288	ASTM D-2983
Flash point, open cup, °C min	200	230	ASTM D-92
Pour point, °C, max.	-27	-30	ASTM D-97
Total base no. mgKOH/g, min	7,5	8,20	ASTM D-2896
Density at 15 °C, kg/l, max.	0.9	0.899	ASTM D-1298

Responsible analyst : Daiva Burbaite

**UAB "SCT LUBRICANTS"**

ŠILUTĖS PL. 119, LT 95112 KLAIPĖDA, LIETUVA  
TEL.: (8 46) 34 03 45, FAX. (8 46) 34 18 91  
E-MAIL: KLAIPEDA@SCT.LT